EXHIBIT "D" UNIVERSAL DESIGN REQUIREMENTS

MHDC requirements for Universal Design of housing for the elderly and single family dwellings.

- 1. Equitable Use a. Flat landing surfaces leading to doorways
- b. Lever action door hardware
- c. Lever action plumbing fixtures controls
- d. No thresholds and/or change of walking surface greater than ½ inch
- 2. Flexibility in Use
- a. Blocking in bathroom walls to accept grab rails
- b. Blocking in or behind shower/tub enclosures to accept grab rails
- c. Door assemblies and cabinet door assemblies that will accept lever or knob hardware without alteration or replacement
- 3. Simple and Intuitive
- a. Buttons on control panels that can be distinguished by touch
- 4. Perceptible Information
- a. Signage with large contrasting print in addition to generally recognized icons
- b. Contrasting colors between wiring devices [receptacles and light switches] and surrounding surfaces
- c. Contrasting colors between steps and landings
- d. Contrasting colors between different floor coverings
- e. Contrasting colors between countertops and flooring
- f. Contrasting colors between plumbing fixtures and flooring/countertops
- 5. Tolerance for Error
- a. Light switches with large flat pads
- b. Non-slip walking surfaces
- 6. Low Physical Effort
- a. Self-closing fire rated doors must be on lowest setting while complying with the enforced building code.
- b. No interior ramps
- 7. Size and space for approach and use
- a. 36 inch wide doors
- b. Goal: 5 feet clear turning circle in kitchen
- c. Goal: 5 feet clear turning circle in bathroom
- d. 42 inch wide residential unit and common hallways

Effective 03/03/2015